

Building Product Information Sheet

Duravit Acrylic Baths

Building Product Information Requirements (BPIR)

Version: 2

Date Created: December 2023

Date Modified: June 2024

Product Name	Duravit Acrylic Baths
Product Lines	Acrylic Freestanding, Back to Wall, Corner and Drop in baths.
Product Identifier(s)	Duravit branded baths including the following ranges: Happy D2 Plus, Starck, XViU,

PRODUCT DESCRIPTION

- Duravit Acrylic baths are either floorstanding, back to wall, corner or drop in style.
- All baths are made from Sanitary grade acrylic, timber base support and fibreglass reinforced for added strength.
- Some baths are supplied with built in overflow, depending on the model.
- Colour White with selected models available in dual colour tones.

SCOPE OF USE

- Acrylic Baths are designed for domestic bathing/cleaning applications.
- Designed to be filled by a Bath Filler (floor mounted) or Wall mounted bath mixer.
- Model determines if Floor standing back to wall, Corner or drop in installation.
- Drop in baths are designed to be installed in a timber support frame.

CONDITIONS OF USE

- Duravit Baths must be installed by a registered trade person and as per the manufacturer's instructions.
- All plumbing to and from the bath must be carried out by a registered plumber and in accordance to AS/NZS3500.2:2021.
- These products are intended for domestic or commercial use.
- Not suitable for accessibility facilities.
- Care should be taken when filling the bath with Hot water (Mixture of Hot/Cold) as per installation instructions.
- Uncontrollable heat source (ie Wet Back systems) are not recommended as water temp above 60deg direct onto the bath surface can cause damage and discolouration.
- Recommended TCV valves with fixed temperature of 55deg recommended as per AS/NZS3500.2:2021 Plumbing Regulations.
- Cleaning shall be done in accordance with the manufacturers cleaning instructions.
- Solvent based cleaners should not be used on any part of the acrylic surface.

RELEVANT BUILDING CODE CLAUSES

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.5

CONTRIBUTIONS TO COMPLIANCE

- B2.3.1 (a) (ii) and (iii) Duravit Sanitary Grade acrylic baths have a durability of at least 10 years when not exposed to direct UV light and where not crushed or knocked in a way that may cause a crack in the acrylic, that may cause a leak.
- F2.3.1: Duravit baths are safe when handle when installed as per the supplied installation instructions. There are no requirements for this product to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.
- G1/AS1 - Acrylic Baths are required to be connected to a waste system to assist the removal of the water as per AS/NZS3500.2:2021 Plumbing Standards and should be installed in accordance with the manufacturer's installation instructions.
- G12/AS1: Water Supply to the bath should be provided in accordance to AS/NZS3500.2:2021 in relation to ensure the supply does not cause backflow or contamination into the potable water system.

SUPPORTING DOCUMENTATION

The following additional documentation supports the above statements:

Title (Type)	Version	URL
Warranty Period	1	https://www.metrix.co.nz/warranty

CONTACT DETAILS

Manufacture location	Overseas (Germany, and other company-owned factories worldwide)
Legal and Trading name of manufacturer	Duravit AG
Manufacturer website	https://www.duravit.com/
Legal and trading name of importer	Metrix Imports Ltd
Importer address for service	Metrix Building, 65 Parnell Rise Auckland 1052
Importer website	www.metrix.co.nz
Importer NZBN	9429033312378
Importer email	Info@metrix.co.nz
Importer phone number	09 379 7399

WARNINGS AND BANS

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

Yes No